





# STANDARD ST EXCAVATOR BUCKETS



This line of excavator buckets is designed for general use in conditions that are not difficult. It can be used particularly when working with easily breakable and less abrasive materials in workability classes 1 to 4 (arable soil, earth, sand, clay, weathered soft limestone and marl).

The bucket shape is optimized for easy penetration into material.





### STANDARD ST EXCAVATOR BUCKETS

## MAIN

# FEATURES AND BENEFITS

Sturdy suspension construction for high strength and resistance against torsion at the critical points where parts connect.

Deep shape for larger volume combined with a smaller distance between pin and teeth for the best transfer of digging force.

The strong body and sides made from a single piece give the bucket design structural integrity.

The ESCO Ultralok™ teeth system provides optimum digging performance.

Armouring on lower part of sides.

Bottom made of abrasion resistant steel with 3 times longer service life with lower weight.





#### www.renomag.cz

**RENOMAG spol. s r. o.,** Cukrovar 1266, Rosice, 664 84 Zastávka u Brna, tel.: +420 546 411 678, e-mail: renomag@renomag.cz **RENOMAG SLOVAKIA spol. s r. o.,** Kopčianska 63, 851 01 Bratislava, tel.: +421 911 401 402, e-mail: info@renomagslovakia.sk